



EVH Series

EVH12150 Datasheet

12V Top Terminal VRLA-AGM

Specifications

| | |
|--|--|
| Voltage (Vdc) | 12 |
| Ah Capacity (8-Hr 1.75 VPC @ 25°C) | 14.08 |
| Ah Capacity (20-Hr 1.75 VPC @ 25°C) | 15.20 |
| Ah Capacity (8-Hr 1.80 VPC @ 25°C) | 13.92 |
| Max Charge Current (A) | 4.50 |
| Max Discharge Current (A) | 180 |
| Short Circuit Current (A) | 576 |
| Internal Resistance (mΩ) | Approx. 10.5 |
| Terminal Type | F2 terminal - Faston Tab 250 |
| Terminal Torque | -- |
| Container Material | ABS (UL 94-HB) |
| Weight (kg. / lb., Approx.) | 4.60 / 10.14 |
| Length (L) (mm / in) | 151.0±2.0 / 5.94±0.08 |
| Width (W) (mm / in) | 98.0±1.0 / 3.86±0.04 |
| Height (H) (mm / in) | 101.8±1.5 / 4.01±0.06 |
| Design Life | 450 cycles @ 100%DOD at 25°C 1800 cycles @ 30%DOD at 25°C |
| Operating Temperature | Nominal: 25°C (77°F) Discharge: -15°C - 50°C (5°F-122°F) Charge/Storage: -15°C - 40°C (5°F - 104°F) |
| Float Charging Voltage | -- |
| Eq. Charging Voltage | 14.4 - 15.0 Vdc/battery 25°C (77°F) |
| Self-Discharge | Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F); Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F). |



Valve Regulated Lead Acid
(VRLA) Battery

Maintenance-Free, Absorbent
Glass Mat (AGM) Technology for
Efficient Gas Recombination of
up to 99%

Pure Lead Construction and
Proprietary Elements

Designed for E-mobility or deep
cycling applications

Built in Accordance with IEC
60254-1:2005 / IEC60254-
2:2008, UL1973 Listed
(MH66728) and UL1989
Recognized (MH14533)

Certified by TUV NORD
according to ISO 9001:2015





EVH Series

EVH12150 Datasheet

12V Top Terminal VRLA-AGM

Constant Current Discharge Characteristics Per Battery: Amperes (25°C, 77°F)

| F.V/Time | 30MIN | 45MIN | 60MIN | 90MIN | 2HR | 3HR | 4HR | 5HR | 6HR | 8HR | 10HR | 20HR |
|-------------------|-------|-------|-------|-------|------|------|------|------|------|------|------|------|
| 10.02V (1.67 VPC) | 19.9 | 14.1 | 11.0 | 7.79 | 6.11 | 4.25 | 3.31 | 2.73 | 2.16 | 1.78 | 1.42 | 0.78 |
| 10.50V (1.75 VPC) | 19.5 | 13.8 | 10.8 | 7.66 | 6.00 | 4.17 | 3.27 | 2.71 | 2.14 | 1.76 | 1.39 | 0.76 |
| 10.80V (1.80 VPC) | 19.0 | 13.8 | 10.7 | 7.50 | 5.83 | 4.08 | 3.19 | 2.64 | 2.10 | 1.74 | 1.38 | 0.75 |

Constant Power Discharge Characteristics Per Battery: Watts (25°C, 77°F)

| F.V/Time | 30MIN | 45MIN | 60MIN | 90MIN | 2HR | 3HR | 4HR | 5HR | 6HR | 8HR | 10HR | 20HR |
|-------------------|-------|-------|-------|-------|------|------|------|------|------|------|------|------|
| 10.02V (1.67 VPC) | 220 | 163 | 128 | 90.8 | 70.5 | 49.2 | 38.6 | 31.7 | 25.2 | 20.9 | 17.0 | 8.96 |
| 10.50V (1.75 VPC) | 215 | 159 | 125 | 88.7 | 69.4 | 48.8 | 38.1 | 31.1 | 24.9 | 20.7 | 16.8 | 8.82 |
| 10.80V (1.80 VPC) | 211 | 157 | 123 | 87.3 | 68.6 | 47.9 | 37.5 | 30.7 | 24.6 | 20.5 | 16.7 | 8.74 |

