



EVX Series

EVX12650 Datasheet

12V Top Terminal VRLA-AGM

Specifications

Voltage (Vdc)	12
Ah Capacity (8-Hr 1.75 VPC @ 25°C)	59.36
Ah Capacity (20-Hr 1.75 VPC @ 25°C)	66.20
Ah Capacity (8-Hr 1.80 VPC @ 25°C)	58.24
Max Charge Current (A)	19.50
Max Discharge Current (A)	500 (5sec)
Short Circuit Current (A)	1568
Internal Resistance	Approx. 4.6 mΩ
Terminal Type	I2 thread lead alloy terminal to accept M6 bolt
Terminal Torque	51.7±10.3 Kgf·cm / 44.9±9.0 Lbf·in / 5.10±1.0 N·m
Container Material	PP (UL 94-HB)
Weight (kg. / lb., Approx.)	22.20 / 48.89
Length (L) (mm / in)	349.4±2.5 / 13.76±0.10
Width (W) (mm / in)	166.0±2.0 / 6.54±0.08
Height (H) (mm / in)	174.9±2.0 / 6.89±0.08
Design Life	400 cycles @ 100%DOD at 25°C 1800 cycles @ 30%DOD at 25°C
Operating Temperature	Nominal: 25°C (77°F) Discharge: -15°C - 50°C (5°F-122°F) Charge/Storage: -15°C - 40°C (5°F - 104°F)
Float Charging Voltage	--
Eq. Charging Voltage	14.4 - 15.0 Vdc/battery 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months and 10 months with equalization charge* at 25C (77F); Full recharging is required before usage, and charged sooner if stored at higher temperature than 25C (77F).



Valve Regulated Lead Acid (VRLA) Battery

Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%

Pure Lead Construction and Proprietary Elements

Designed for E-mobility or deep cycling applications

Built in Accordance with IEC 60254-1:2005 / IEC60254-2:2008, UL1973 Listed (MH66728) and UL1989 Recognized (MH14533)

Certified by TUV NORD according to ISO 9001:2015





EVX Series

EVX12650 Datasheet


12V Top Terminal VRLA-AGM

Constant Current Discharge Characteristics Per Battery: Amperes (25°C, 77°F)


F.V/Time	30MIN	45MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
10.02V (1.67 VPC)	69.9	51.2	41.1	29.8	23.7	16.9	13.3	11.0	9.50	7.54	6.28	3.35
10.50V (1.75 VPC)	68.3	50.2	40.4	29.4	23.4	16.7	13.1	10.8	9.34	7.42	6.16	3.31
10.80V (1.80 VPC)	65.7	48.7	39.4	28.8	23.0	16.4	12.9	10.7	9.22	7.28	6.04	3.23

Constant Power Discharge Characteristics Per Battery: Watts (25°C, 77°F)

F.V/Time	30MIN	45MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
10.02V (1.67 VPC)	804	595	481	351	277	198	157	130	113	89.6	74.3	40.2
10.50V (1.75 VPC)	784	585	475	347	275	196	155	128	111	88.2	73.2	39.7
10.80V (1.80 VPC)	759	571	467	342	270	193	151	127	110	86.9	72.0	38.9



Detail A Drawing(3:1)



[M6 bolt & nut]

