



MSJ Series

MSJ-200 Datasheet

2V VRLA-AGM

Specifications

Voltage (Vdc)	2
Ah Capacity (8-Hr 1.75 VPC @ 25°C)	202.40
Ah Capacity (20-Hr 1.75 VPC @ 25°C)	210.00
Ah Capacity (8-Hr 1.80 VPC @ 25°C)	197.60
Max Charge Current (A)	60.00
Max Discharge Current (A)	1200 (5sec)
Short Circuit Current (A)	3939
Internal Resistance	Approx. 0.42 mΩ
Terminal Type	I4 thread copper alloy terminal to accept M8 bolt
Terminal Torque	126±25 Kgf·cm / 109±22 Lbf·in / 12.3±2.5 N·m
Container Material	Flame Retardant ABS (UL 94-V0)
Weight (kg. / lb., Approx.)	15.00 / 33.04
Depth (D) (mm / in)	170.0±2.0 / 6.69±0.08
Width (W) (mm / in)	106.0±1.5 / 4.17±0.06
Height (H) (mm / in)	339.0±2.5 / 13.15±0.10
Design Life	Up to 20 Years in Standby Service at 25°C. Eurobat (20°C): >12 Years Very Long Life
Operating Temperature	Nominal: 25°C (77°F) Discharge: -15°C - 50°C (5°F-122°F) Charge/Storage: -15°C - 40°C (5°F - 104°F)
Float Charging Voltage	2.21 ~ 2.25 Vdc/battery 25°C (77°F)
Eq. Charging Voltage	2.35 Vdc/battery 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months and 10 months with equalization charge* at 25C (77F); Full recharging is required before usage, and charged sooner if stored at higher temperature than 25C (77F).



Valve Regulated Lead Acid (VRLA) Battery

Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%

Pure Lead Construction and Proprietary Elements

Designed for High-Capacity Float Service Standby Power Applications

Built in Accordance with IEC 60896-21/22:2004, UL1973 Listed (MH66728) and UL1989 Recognized (MH14533)

Certified by TUV NORD according to ISO 9001:2015





MSJ Series

MSJ-200 Datasheet

2V VRLA-AGM

Constant Current Discharge Characteristics Per Battery: Amperes (25°C, 77°F)

F.V/Time	15MIN	30MIN	60MIN	2HR	2.5HR	3HR	5HR	6HR	8HR	10HR	20HR	24HR
1.67V	332	236	148	86.0	71.7	61.7	38.9	33.0	25.8	21.4	10.7	8.9
1.75V	281	208	138	83.3	69.7	60.2	38.1	32.3	25.3	21.0	10.5	8.7
1.80V	240	184	127	79.7	67.0	58.1	36.9	31.4	24.7	20.5	10.2	8.5

Constant Power Discharge Characteristics Per Battery: Watts (25°C, 77°F)

F.V/Time	15MIN	30MIN	60MIN	2HR	2.5HR	3HR	5HR	6HR	8HR	10HR	20HR	24HR
1.67V	603	433	271	165	137	118	77.6	66.5	50.9	39.8	19.9	16.6
1.75V	529	394	256	160	134	116	76.3	65.4	49.9	39.1	19.5	16.3
1.80V	475	356	239	154	129	112	74.4	63.8	48.4	38.0	19.0	15.8

Detail A Drawing(3:1)

