



MSV Series

MSV-800 Datasheet

2V VRLA-AGM

Specifications

Voltage (Vdc)	2
Ah Capacity (8-Hr 1.75 VPC @ 25°C)	784.00
Ah Capacity (20-Hr 1.75 VPC @ 25°C)	820.00
Ah Capacity (8-Hr 1.80 VPC @ 25°C)	768.00
Max Charge Current (A)	240.00
Max Discharge Current (A)	4800 (5sec)
Short Circuit Current (A)	--
Internal Resistance	Approx. 0.38 mΩ
Terminal Type	I4 thread copper alloy terminal to accept M8 bolt
Terminal Torque	126±25 Kgf·cm / 109±22 Lbf·in / 12.3±2.5 N·m
Container Material	Flame Retardant ABS (UL 94-V0)
Weight (kg. / lb., Approx.)	50.60 / 111.52
Length (L) (mm / in)	373.0±2.5 / 14.69±0.10
Width (W) (mm / in)	174.0±2.0 / 6.85±0.08
Height (H) (mm / in)	339.0±2.5 / 13.15±0.10
Design Life	Up to 15 Years in Standby Service at 25°C. Eurobat (20°C): >12 Years Very Long Life
Operating Temperature	Nominal: 25°C (77°F) Discharge: -15°C - 50°C (5°F-122°F) Charge/Storage: -15°C - 40°C (5°F - 104°F)
Float Charging Voltage	2.21 ~ 2.25 Vdc/battery 25°C (77°F)
Eq. Charging Voltage	2.35 Vdc/battery 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months and 10 months with equalization charge* at 25C (77F); Full recharging is required before usage, and charged sooner if stored at higher temperature than 25C (77F).



Valve Regulated Lead Acid (VRLA) Battery

Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%

Pure Lead Construction and Proprietary Elements

Designed for High-Capacity Float Service Standby Power Applications

Built in Accordance with IEC 60896-21/22:2004, UL1973 Listed (MH66728) and UL1989 Recognized (MH14533)

Certified by TUV NORD according to ISO 9001:2015





MSV Series

MSV-800 Datasheet


2V VRLA-AGM

Constant Current Discharge Characteristics Per Battery: Amperes (25°C, 77°F)

F.V/Time	15MIN	30MIN	60MIN	2HR	2.5HR	3HR	5HR	6HR	8HR	10HR	20HR	24HR
1.67V	1038	746	494	296	250	218	148	128	104	88.0	44.0	36.7
1.75V	842	671	448	274	232	202	138	120	98.0	82.0	41.0	34.2
1.80V	732	587	422	264	223	194	134	118	96.0	80.0	40.0	33.3

Constant Power Discharge Characteristics Per Battery: Watts (25°C, 77°F)

F.V/Time	15MIN	30MIN	60MIN	2HR	2.5HR	3HR	5HR	6HR	8HR	10HR	20HR	24HR
1.67V	1707	1318	920	550	468	410	280	246	198	166	83.0	69.2
1.75V	1473	1191	832	514	439	386	266	232	190	160	80.0	66.7
1.80V	1343	1066	784	494	421	370	258	226	184	158	79.0	65.8



Detail A Drawing(3:1)

