



XTV-WT Series

XTV12120F2FR-WT Datasheet

12V Top Terminal VRLA-AGM

Specifications

Voltage (Vdc)	12
Ah Capacity (8-Hr 1.75 VPC @ 25°C)	11.3
Ah Capacity (20-Hr 1.75 VPC @ 25°C)	12.0
Ah Capacity (8-Hr 1.80 VPC @ 25°C)	11.1
Max Charge Current (A)	3.60
Max Discharge Current (A)	180
Short Circuit Current (A)	438
Internal Resistance (mΩ)	Approx. 15.0
Terminal Type	F2 terminal - Faston Tab 250
Terminal Torque	--
Container Material	ABS Flame Retardant (94-V0)
Weight (kg. / lb., Approx.)	4.10 / 9.02
Length (L) (mm / in)	151.0±2.0 / 5.94±0.08
Width (W) (mm / in)	98.0±1.0 / 3.86±0.04
Height (H) (mm / in)	101.8±1.5 / 4.01±0.06
Design Life	Up to 12 Years in Standby Service at 25°C. Eurobat (20°C): >12 Years Very Long Life
Operating Temperature	Nominal: 25°C (77°F) Discharge/Charge: -20°C - 50°C (-4°F-122°F) Storage: -15°C - 40°C (5°F - 104°F)
Float Charging Voltage	13.5 - 13.8 Vdc/battery 25°C (77°F)
Eq. Charging Voltage	14.4 - 15.0 Vdc/battery 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F); Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F).



Valve Regulated Lead Acid (VRLA) Battery

Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%

Pure Lead Construction and Proprietary Elements

Designed for Wind Turbine Applications

Built in Accordance with IEC 61056-1/2:2012, UL1973 Listed (MH66728) and UL1989 Recognized (MH14533)

Certified by TUV NORD according to ISO 9001:2015





XTV-WT Series

XTV12120F2FR-WT Datasheet

12V Top Terminal VRLA-AGM

Constant Current Discharge Characteristics Per Battery: Amperes (25°C, 77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	90MIN	2HR	3HR	5HR	8HR	10HR	20HR
10.02V (1.67 VPC)	49.8	30.9	22.9	13.4	7.85	5.74	4.54	3.26	2.13	1.42	1.17	0.62
10.50V (1.75 VPC)	45.2	29.3	22.2	13.2	7.75	5.68	4.49	3.23	2.11	1.40	1.15	0.60
10.80V (1.80 VPC)	40.3	27.4	22.1	12.8	7.61	5.59	4.43	3.19	2.07	1.39	1.14	0.59

Constant Power Discharge Characteristics Per Battery: Watts (25°C, 77°F)

F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	90MIN	2HR	3HR	5HR	8HR	10HR	20HR
10.02V (1.67 VPC)	538	351	267	155	91.7	67.3	53.5	38.8	25.6	17.1	14.1	7.55
10.50V (1.75 VPC)	495	337	260	153	90.9	66.7	53.1	38.5	25.4	16.9	13.9	7.49
10.80V (1.80 VPC)	454	319	248	150	89.7	65.9	52.5	38.0	25.1	16.8	13.8	7.39

