



Calor XHT-FT Series

XHT7700FT Datasheet

12V Front Terminal VRLA-AGM

Specifications

Voltage (Vdc)	12V
Watts Per Cell (30-Sec to 1.67VPC @25°C)	2033.83
Watts Per Cell (5-Min to 1.67VPC @25°C)	1239.33
Watts Per Cell (15-Min to 1.67VPC @25°C)	719.66
Max Charge Current (A)	64.2 (5 sec)
Max Discharge Current (A)	1680 (5 sec)
Short Circuit Current (A)	4631 (5 sec)
Internal Resistance (mΩ)	Approx. 1.84 mΩ
Terminal Type	I2 thread alloy terminal to accept M6 bolt
Terminal Torque	51.7±10.3 kgf·cm / 44.9±9.0 lbf·in 5.1±1.0 N·m
Container Material	Flame-Retardant Polymer Material (UL 94-V0)
Weight (kg. / lb.)	Approx. 54.0kg / 119.05lb
Length (L) (mm / in)	558.0 ± 2.5mm / 21.97 ± 0.10in
Width (W) (mm / in)	126.0 ± 1.5mm / 4.96 ± 0.06in
Height (H) (mm / in)	255.0 ± 2.5mm / 10.04 ± 0.10in
Design Life	12+ Years in Standby Service at 25°C; Up to 10 Years in Standby Service at 35°C
Operating Temperature	Nominal: 25°C (77°F) Discharge: -40°C - 65°C (-40°F - 149°F) Charge / Storage -40°C - 65°C (-40°F - 149°F)
Float Charging Voltage	13.5 - 13.8VDC / battery @ 25°C (77°F)
Eq. Charging Voltage	14.4 - 15.0VDC / battery @ 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months & 10 months with equalization charge @ 25°C (77°F). Full recharge required before use. Charge sooner if stored above 25°C (77°F).



KEY FEATURES

- Valve Regulated Lead Acid (VRLA) Battery Constructed with High Durability Material (UL 94-V0)
- Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%
- Pure Lead Construction and Catalyst 2X Proprietary Additive Technology

APPLICATIONS

- Designed for High-Rate & High-Temperature Standby Service
- Optimized for Harsh Environments with Extended Service Life

SAFETY & COMPLIANCE

- Built in Accordance with IEC 60896-21/22:2004
- UL1973 Listed (MH66728)
- UL1989 Recognized (MH14533)
- Certified by TUV NORD according to ISO 9001:2015



© 2026 CSB Energy Technology Co., Ltd. All Rights Reserved.

CSB Energy Technology Co., Ltd. reserves the right to change specifications or design without notice. Visit csb-battery.com for the latest information.



Calor XHT-FT Series

XHT7700FT Datasheet

12V Front Terminal VRLA-AGM

Constant Current Discharge Characteristics Per Battery: Amperes (25°C / 77°F)

F.V/Time	30SEC	60SEC	2MIN	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	45MIN	60MIN	90MIN
10.02V (1.67VPC)	1086	1046	971	726	583	520	397	323	231	164	127	89.6
10.50V (1.75VPC)	887	865	815	629	521	462	365	300	220	160	124	87.6
10.80V (1.80VPC)	728	707	687	557	466	417	339	276	207	152	119	84.8



Constant Power Discharge Characteristics Per Battery: Watts (25°C / 77°F)

F.V/Time	30SEC	60SEC	2MIN	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	45MIN	60MIN	90MIN
10.02V (1.67VPC)	12203	11093	9888	7436	6121	5408	4318	3535	2590	1882	1475	1046
10.50V (1.75VPC)	10271	9528	8516	6640	5523	4963	4084	3326	2491	1835	1442	1027
10.80V (1.80VPC)	8521	8269	7547	6128	5044	4598	3766	3109	2373	1761	1392	998

Line Drawing



Detail A Drawing(4:1)



© 2026 CSB Energy Technology Co., Ltd. All Rights Reserved.

CSB Energy Technology Co., Ltd. reserves the right to change specifications or design without notice. Visit csb-battery.com for the latest information.